


# CF FLOODLIGHT

250 MV ■ 400 MV ■ 250 HPS ■ 400 HPS ■ 250 MH ■ 400 MH



## APPLICATIONS

SECURITY  
SMALL SPORTS AREAS  
CAR PARKS  
WORK AREAS  
ILLUMINATION OF BUILDINGS

**MOUNTING HEIGHT:** 5 - 9 m

- powder coated cast aluminium housing
- heat tempered glass
- separate control gear compartment
- mild steel wall mount powder coated stirrup - optional pole clamp
- IP55

## ORDERING DATA

| CODE              | CORRECTED LINE CURRENT |         | WEIGHT   |
|-------------------|------------------------|---------|----------|
|                   | STARTING               | RUNNING |          |
| CF <b>250</b> MV  | 2.60 A                 | 1.35 A  | 8.25 KG  |
| CF <b>400</b> MV  | 4.20 A                 | 2.10 A  | 10.30 KG |
| CF <b>250</b> HPS | 2.10 A                 | 1.42 A  | 8.90 KG  |
| CF <b>400</b> HPS | 3.80 A                 | 2.20 A  | 10.55 KG |
| CF <b>250</b> MH  | 2.80 A                 | 1.42 A  | 8.90 KG  |
| CF <b>400</b> MH  | 3.80 A                 | 2.20 A  | 10.55 KG |