

CDB BULKHEAD

80 MV ■ 125 MV ■ 70(I) HPS ■ 150 HPS ■ 70 MH ■ 150 MH



APPLICATIONS

TUNNELS
PERIMETER
SMALL AREAS
ARCHITECTURAL
CONVEYOR

MOUNTING HEIGHT: 2.5 - 5 m



- powder coated cast aluminium housing
- borosilicate glass diffuser
- integral control gear
- wall mounted
- stainless steel screws
- IP55
- also available in 2 x 26 W & emergency

ORDERING DATA

CODE	CORRECTED LINE CURRENT		WEIGHT
	STARTING	RUNNING	
CDB 80 MV	0.90 A	0.45 A	5.15 KG
CDB 125 MV	1.35 A	0.68 A	5.60 KG
CDB 70(I) HPS	0.72 A	0.45 A	5.90 KG
CDB 150 HPS	1.30 A	0.88 A	6.95 KG
CDB 70 MH	0.72 A	0.45 A	5.90 KG
CDB 150 MH	1.70 A	0.82 A	6.95 KG

CIB INDUSTRIAL BULKHEAD

80 MV ■ 125 MV ■ 70(I) HPS ■ 150 HPS ■ 70 MH ■ 150 MH



APPLICATIONS

TUNNELS
CORRIDORS
BUILDING PERIMETER
CONVEYER
CANOPY

MOUNTING HEIGHT: 2.5 - 5 m

- robust powder coated cast aluminium housing
- borosilicate glass diffuser
- integral control gear
- ceiling/wall mounting
- stainless steel clips
- IP65
- also available in 2 x 26 W & emergency

ORDERING DATA

CODE	CORRECTED LINE CURRENT		WEIGHT
	STARTING	RUNNING	
CIB 80 MV	0.90 A	0.45 A	8.70 KG
CIB 125 MV	1.35 A	0.68 A	9.00 KG
CIB 70(I) HPS	0.72 A	0.45 A	8.70 KG
CIB 150 HPS	1.30 A	0.88 A	10.00 KG
CIB 70 MH	0.72 A	0.45 A	9.00 KG
CIB 150 MH	1.70 A	0.82 A	10.50 KG