


RFM FLUORESCENT MOISTURE PROOF

1 x 18 W ■ 2 x 18 W ■ 1 x 36 W ■ 2 x 36 W ■ 1 x 58 W ■ 2 x 58 W



APPLICATIONS

CORRIDORS & PASSAGEWAYS
MOISTURE/CORROSIVE
ENVIRONMENT
DUSTY ENVIRONMENT
CANOPY
COLD ROOMS

MOUNTING HEIGHT: 2 - 4 m

- GRP base
- acrylic diffuser
- robust polyamide or stainless steel clips
- roto lock lampholders
- removable powder coated gear plate
- electromagnetic or electronic control gear
- IP66
- T8 or T5 lamps

ORDERING DATA

CODE	CORRECTED LINE CURRENT		WEIGHT
	STARTING	RUNNING	
RFM 118 (1 X 18 W)	0.17 A	0.13 A	1.50 KG
RFM 218 (2 X 18 W)	0.29 A	0.22 A	2.00 KG
RFM 136 (1 X 36 W)	0.29 A	0.22 A	3.00 KG
RFM 236 (2 X 36 W)	0.58 A	0.44 A	4.00 KG
RFM 158 (1 X 58 W)	0.42 A	0.32 A	3.50 KG
RFM 258 (2 X 58 W)	0.84 A	0.64 A	5.00 KG