




MODEL	HIGH POWER LED FLOOD LIGHT (120W)			CF 120LED
PICTURES	US Epistar LED Chip Meanwell Driver CE, ROHS compliant 2 year warranty			Applications: Security, signage, perimeters
OPTICAL PARAMETERS	LED Power	2X60W	System Consumptions	130W
	LED Chip	2 X US Epistar (60W)	LED Initial Flux	9600Lumens
	THD	<20%	LED Maintain Flux (After the lens and thermal stabilization)	6480Lumens
	Color Rendering Index	Pure White: Ra > 75	Illumination area *Pure White 6500K	Mount Height : Distance 6M : 10M 8M : 15M 10M : 20M
	Light Distribution Curve	Rectangular Facular	Illuminance Uniformity	>0.8
	Color Temperature	PW 6000K-6700K	Beam Angle	120°:The Horizontal Axis:110°, The Vertical Axis:45°;
ELECTRICAL PARAMETERS	Input Voltage	AC85V-AC265V	Working Voltage	DC36V
	Frequency Range	50-60 HZ	Power Factor	> 0.93
	Power Efficiency	>87%	Lamp Efficiency	>85%
	IP Grade	IP65	TJ	60 °C ±10 %
	Photocell On/Off	Optional	Dimming Control	Optional
MECHANICAL PARAMETERS	Dimensions	36*29 *21.5cm	Net Weight	7.45KG
	Material	Die-cast aluminum + tempered glass	Working Environment	Temp: -40°C ~ 55°C Humid:10%-90%
	Working Life-span	50000 Hours	Storage Environment	Temp: -20°C ~75°C (25°C best)
PACKING INFORMATION	Packing: 1 pc/ Carton Carton Size: 45.4*35.5*15.3cm			Gross weight:7.5kg