


# RL254 S SUPERBAY

250 MV ■ 400 MV ■ 250 HPS ■ 400 HPS ■ 250 MH ■ 400 MH



## APPLICATIONS

WAREHOUSES

FOUNDRIES

FACTORIES

WORKSHOPS & OTHER  
INDUSTRIAL INSTALLATIONS

**MOUNTING HEIGHT:** 5 m +

- powder coated mild steel gear housing ■ removable gear tray
- 520mm anodised aluminium reflector with optional glass cover ■ IP23 open ■ IP43 enclosed
- **also available with:** 22" acrylic diffuser with optional acrylic drop lens with aluminium adapter

## ORDERING DATA

CODE	CORRECTED LINE CURRENT		WEIGHT
	STARTING	RUNNING	
RL254 S <b>250</b> MV	2.60 A	1.35 A	7.30 KG
RL254 S <b>400</b> MV	4.20 A	2.10 A	8.30 KG
RL254 S <b>250</b> HPS	2.10 A	1.42 A	8.50 KG
RL254 S <b>400</b> HPS	3.80 A	2.20 A	9.85 KG
RL254 S <b>250</b> MH	2.80 A	1.42 A	8.50 KG
RL254 S <b>400</b> MH	3.80 A	2.20 A	9.85 KG