


# RL254 E ECONOBAY

250 MV ■ 400 MV ■ 250 HPS ■ 400 HPS ■ 250 MH ■ 400 MH



## APPLICATIONS

WAREHOUSES  
FOUNDRIES  
FACORIES  
WORKSHOPS & OTHER  
INDUSTRIAL INSTALLATIONS  
**MOUNTING HEIGHT:** 8 m +


- powder coated mild steel gear housing ■ removable gear tray
- 420mm anodised aluminium reflector with optional glass cover ■ IP23 open ■ IP43 enclosed
- **also available with:** 16" acrylic diffuser with optional acrylic drop lens with aluminium ring adapter

## ORDERING DATA

CODE	CORRECTED LINE CURRENT		WEIGHT
	STARTING	RUNNING	
RL254 E 250 MV	2.60 A	1.35 A	6.80 KG
RL254 E 400 MV	4.20 A	2.10 A	7.75 KG
RL254 E 250 HPS	2.10 A	1.42 A	8.00 KG
RL254 E 400 HPS	3.80 A	2.20 A	9.50 KG
RL254 E 250 MH	2.80 A	1.42 A	8.00 KG
RL254 E 400 MH	3.80 A	2.20 A	9.50 KG

# RL254 S SUPERBAY

250 MV ■ 400 MV ■ 250 HPS ■ 400 HPS ■ 250 MH ■ 400 MH



## APPLICATIONS

WAREHOUSES  
FOUNDRIES  
FACORIES  
WORKSHOPS & OTHER  
INDUSTRIAL INSTALLATIONS  
**MOUNTING HEIGHT:** 5 m +


- powder coated mild steel gear housing ■ removable gear tray
- 520mm anodised aluminium reflector with optional glass cover ■ IP23 open ■ IP43 enclosed
- **also available with:** 22" acrylic diffuser with optional acrylic drop lens with aluminium ring adapter

## ORDERING DATA

CODE	CORRECTED LINE CURRENT		WEIGHT
	STARTING	RUNNING	
RL254 S 250 MV	2.60 A	1.35 A	7.30 KG
RL254 S 400 MV	4.20 A	2.10 A	8.30 KG
RL254 S 250 HPS	2.10 A	1.42 A	8.50 KG
RL254 S 400 HPS	3.80 A	2.20 A	9.85 KG
RL254 S 250 MH	2.80 A	1.42 A	8.50 KG
RL254 S 400 MH	3.80 A	2.20 A	9.85 KG

# RL254 E/S ENERGY SAVING HIGHBAY

85 W ■ 105 W



## APPLICATIONS

WAREHOUSES  
FOUNDRIES  
FACTORIES  
WORKSHOPS & OTHER  
INDUSTRIAL INSTALLATIONS  
**MOUNTING HEIGHT:** 5 - 6 m

- corrosion resistant glass reinforced polyester mounting cup with gland, eyebolt and 3m cord
- 420/520mm anodised aluminium reflector with optional glass cover ■ IP23 open ■ IP43 enclosed
- 16"/22" acrylic diffuser with aluminium adapter - acrylic cover optional

## ORDERING DATA

CODE	CORRECTED LINE CURRENT		WEIGHT
	STARTING	RUNNING	
RL254 E <b>85</b> CFL	0.6 A	0.38 A	1.56 KG
RL254 E <b>105</b> CFL	0.9 A	0.44 A	1.56 KG
RL254 S <b>85</b> CFL	0.6 A	0.38 A	1.88 KG
RL254 S <b>105</b> CFL	0.9 A	0.44 A	1.88 KG