

SURFACE FLUORESCENT T8/T5

1 x 18 W ■ 2 x 18 W ■ 1 x 36 W ■ 2 x 36 W ■ 1 x 58 W ■ 2 x 58 W



An efficient yet low cost channel type luminaire available for use with bi-pin fluorescent lamps.

- **Body:** Formed sheet steel finish with white epoxy powder coating
- **Lampholders:** Roto-lock or Telescopic type
- **Ballast:** ECG is standard, other options available on request
- **Other:** One piece aluminium wing available

APPLICATIONS

UNDER COVER PARKING
UNDER COVER WALKWAYS
OFFICES
FACTORIES
DOMESTIC
WORKSHOPS
MOUNTING HEIGHT: 2 - 4 m

ORDERING DATA

CODE	LAMP	LENGTH	WIDTH	HEIGHT	FIXING	WEIGHT
PSQ-118-ECG	1 x 18	620 mm	70 mm	45 mm	435 mm	1.20 KG
PSQ-136-ECG	1 x 36	1230 mm	70 mm	45 mm	1020 mm	2.00 KG
PSQ-158-ECG	1 x 58	1530 mm	70 mm	45 mm	1320 mm	2.50 KG
PSQ-218-ECG	2 x 18	620 mm	70 mm	45 mm	435 mm	1.30 KG
PSQ-236-ECG	2 x 36	1230 mm	70 mm	45 mm	1020 mm	2.00 KG
PSQ-258-ECG	2 x 58	1530 mm	70 mm	45 mm	1320 mm	2.50 KG