


X-RANGE LED FLOOD


Product details



50W



100W



150W





200W



300W



400W



600W

Features

- Available in different optics and wattages.
- Marine grade aluminium and highly corrosive resistant to sea and salt conditions.
- Cover mad of high impact acrylic.
- Can be used as a floodlight.

Benefits

- Energy saving.
- Easy installation and maintenance.
- Ingress protection rating - IP65.

Applications

Warehouses
Workshops
Garage canopies
Factories

Warranty

3 year warranty

X-RANGE LED FLOOD

Specifications

Product Code	X-RANGEFL50W	X-RANGEFL100W	X-RANGEFL150W
Approx System Wattage	50W	100W	150W
Absolute Lumens	5250lm	10500lm	15750lm
Colour Temperature	4500K	4500K	4500K
CRI	≥75	≥75	≥75
Life Span	50000hrs	50000hrs	50000hrs
Average temp	min -40° max -50°	min -40° max -50°	min -40° max -50°
Housing Material	Aluminium 6063 and high impact acrylic cover.	Aluminium 6063 and high impact acrylic cover	Aluminium 6063 and high impact acrylic cover
Packaging Weights and dimensions	320mm x 125mm x 50mm	635mm x 120mm x 50mm	970mm x 120mm x 50mm
Photometric distribution	Asymetric	Asymetric	Asymetric
IP Rating	IP 65	IP 65	IP 65
Power Factor	0.97	0.97	0.97
lm/W	105lm/W	105lm/W	105lm/W
Suggested mounting height	3 - 5m Max	6 - 7m Max	7 - 9m Max

X-RANGE LED FLOOD

Specifications

Product Code	X-RANGEFL200W	X-RANGEFL300W	X-RANGEFL400W
Approx System Wattage	200W	300W	400W
Absolute Lumens	21000lm	31000lm	42000lm
Colour Temperature	4500K	4500K	4500K
CRI	≥75	≥75	≥75
Life Span	50000hrs	50000hrs	50000hrs
Average temp	min -40° max -50°	min -40° max -50°	min -40° max -50°
Housing Material	Aluminium 6063 and high impact acrylic cover.	Aluminium 6063 and high impact acrylic cover.	Aluminium 6063 and high impact acrylic cover.
Packaging Weights and dimensions	635mm x 245mm x 50mm	635mm x 370mm x 50mm	635mm x 495mm x 50mm
Photometric distribution	Asymetric	Asymetric	Asymetric
IP Rating	IP 65	IP 65	IP 65
Power Factor	0.97	0.97	0.97
lm/W	105lm/W	105lm/W	105lm/W
Suggested mounting height	9 - 12m Max	13 - 15m Max	15 - 18m Max

X-RANGE LED FLOOD

Specifications

Product Code	X-RANGEFL600W
Approx System Wattage	600W
Absolute Lumens	63000lm
Colour Temperature	4500K
CRI	≥75
Life Span	50000hrs
Average temp	min -40° max -50°
Housing Material	Aluminium 6063 and high impact acrylic cover.
Packaging Weights and dimensions	635mm x 245mm x 50mm
Photometric distribution	Asymetric
IP Rating	IP 65
Power Factor	0.97
lm/W	105lm/W
Suggested mounting height	18 - 20m Max

