




## CF1000/2000W DIE-CAST FLOODLIGHT

### Product details



90°

### Features

- Die-cast aluminium body.
- Tempered safety glass - Special ceramic glass (2KW)
- External control gear compartment.
- High purity aluminium reflector.
- Heat resistant silicon rubber seal ring.

### Benefits

- Mild steel powder coated stirrup.
- Protractor for aiming angles
- Ingress protection rating - IP 65.

### Applications

Security  
Sport fields  
Car parks  
Large work areas  
Dock, railway & container yards  
High mast installations

### Warranty

3 year warranty

## CF1000/2000W DIE-CAST FLOODLIGHT

### Specifications

Product Code	CF1000MH/HPS	CF2000EMH165SP
Approx System Wattage	1000W - E40	2000W External Ignitor - 16.5A (230V)
Absolute Lumens	80000lm ( MH) - 130000lm ( HPS)	200000lm
Colour Temperature	4800K	4800K
CRI	≥80	≥80
Life Span	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°
Housing Material	Grey powder coated cast aluminium	Grey powder coated cast aluminium
Packaging Weights and dimensions	740mm x 480mm x 235mm @ 30.70Kg	740mm x 480mm x 235mm @ 30.70Kg
Beam Angle	90°	90°
IP Rating	IP 55	IP 55
Power Factor	0.95	0.95
Starting /Running Amp	(8.80 A - 5.50 A) - ( 9.60 A - 5.20 A)	(11.80 - 10.90 A)
Suggested mounting height	12 - 30m Max	12 - 30m Max

## CF1000/2000 DIE-CAST FLOODLIGHT

### Specifications

Product Code	CF2000IMH883P	CF2000EMH883P
Approx System Wattage	2000W Internal Ignitor - 8.8A (380V)	2000W External Ignitor - 8.8A (380V)
Absolute Lumens	200000lm	200000lm
Colour Temperature	4800K	4800K
CRI	≥80	≥80
Life Span	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°
Housing Material	Grey powder coated cast aluminium	Grey powder coated cast aluminium
Packaging Weights and dimensions	740mm x 480mm x 235mm @ 30.70Kg	740mm x 480mm x 235mm @ 30.70Kg
Beam Angle	90°	90°
IP Rating	IP 55	IP 55
Power Factor	0.95	0.95
Starting /Running Amp	(11.40 A - 7.50 A)	(11.40 A - 7.50 A)
Suggested mounting height	12 - 30m Max	12 - 30m Max

## CF1000/2000 DIE-CAST FLOODLIGHT

### Specifications

Product Code	CF2000IMH1033P	CF2000EMH1033P
Approx System Wattage	2000W Internal Ignitor - 10.3A (380V)	2000W External Ignitor - 10.3A (380V)
Absolute Lumens	200000lm	200000lm
Colour Temperature	4800K	4800K
CRI	≥80	≥80
Life Span	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°
Housing Material	Grey powder coated cast aluminium	Grey powder coated cast aluminium
Packaging Weights and dimensions	740mm x 480mm x 235mm @ 30.70Kg	740mm x 480mm x 235mm @ 30.70Kg
Beam Angle	90°	90°
IP Rating	IP 55	IP 55
Power Factor	0.95	0.95
Starting /Running Amp	(8.90A - 6.30 A)	(8.90A - 6.30 A)
Suggested mounting height	12 - 30m Max	12 - 30m Max