


RECTANGULAR BULKHEAD


Product details



40mm
74mm



114mm



225mm

121mm

Features

- Polycarbonate base.
- Polycarbonate diffuser.
- Integral control gear.
- Available in ECG.
- Photocell option.

Benefits

- Ceiling /Wall mounted.
 - UV stabilised for long life
 - Indoor or outdoor use.
 - Available with day-night sensor.
- Ingress protection rating - IP 65.

Applications

Corridors
Entrances & exits
Commercial buildings
Domestic
Staircases
Hospitals & schools

Warranty

3 year warranty

RECTANGULAR BULKHEAD

Specifications

Product Code	MBREC109WGP	MBREC209W1GP	MBREC60/100ESGP - MBREC60/100BCGP
Approx System Wattage	9W - 2 PIN	2x9W - 2 PIN	60W - ES
Absolute Lumens	600lm	12000lm	600lm
Colour Temperature	4800K	4800K	2700K
CRI	≥80	≥80	≥80
Life Span	TBA	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°	min -20° max +35°
Housing Material	Polycarbonate base and diffuser	Polycarbonate base and diffuser	Polycarbonate base and diffuser
Packaging Weights and dimensions	250mm x 150mm x 120mm @ 0.60Kg	250mm x 150mm x 120mm @ 0.86Kg	250mm x 150mm x 120mm @ 0.60Kg
Beam Angle	90°	90°	90°
IP Rating	IP 65	IP 65	IP 65
Power Factor	0.95	0.95	0.95
Lamp	2Pin PL lamp - 0.06 A	2 x 2Pin PL lamp - 0.12 A	60W ES/BC Incandescent
Suggested mounting height	2.5 - 5m Max	2.5 - 5m Max	2.5 - 5m Max