




## RL045 FLOODLIGHT

### Product details



### Features

- Corrosion resistant glass reinforced polyester housing.
- Heat tempered glass.
- High purity aluminium reflector.

### Benefits

- Universal electroplated mounting stirrup with pole clamp.
- Ingress protection rating - IP 65.
- Black or white color options.
- Compact.

### Applications

Security  
Perimeters  
Signage  
Gardens

### Warranty

Reeflite glass reinforced polyester (GRP) housings are guaranteed for 15 years against deterioration due to ultra-violet radiation, hail damage and corrosion at coastal areas.

## RL045 FLOODLIGHT

### Specifications

|                                  |                               |
|----------------------------------|-------------------------------|
| Product Code                     | RL045CFL                      |
| Approx System Wattage            | 45W CFL - E27                 |
| Absolute Lumens                  | 2900lm                        |
| Colour Temperature               | 6500K                         |
| CRI                              | ≥80                           |
| Life Span                        | TBA                           |
| Average temp                     | min -20° max +35°             |
| Housing Material                 | Fibreglass                    |
| Packaging Weights and dimensions | 332mm x 213mm x 260mm @ 2.0Kg |
| Beam Angle                       | 90°                           |
| IP Rating                        | IP 65                         |
| Power Factor                     | 0.95                          |
| Lamp                             | 45W E27 - Energy saving       |
| Suggested mounting height        | 2 - 3m Max                    |