




## RL606 LOWBAY

### Product details



### Features

- Powder coated mild steel body.
- High purity aluminium reflector.
- Integral control gear.
- Glass cover available.

### Benefits

- Mounting brackets.
- Ingress protection rating - IP 23 open.
- Ingress protection rating - IP 43 enclosed.

### Applications

Warehouses  
Foundries  
Factories  
Workshops  
Garage canopies

### Warranty

3 year warranty

## RL606 LOWBAY

### Specifications

Product Code	RL606250MV	RL606400MV
Approx System Wattage	250W MV - E40	400W MV ( E40)
Absolute Lumens	12700lm	22000lm (400w)
Colour Temperature	4800K	4800K
CRI	≥80	≥80
Life Span	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°
Housing Material	Powder coated mild steel body	Powder coated mild steel body
Packaging Weights and dimensions	353mm x 178mm x 616mm @ 7.0Kg	353mm x 178mm x 616mm @ 8.0Kg
Beam Angle	90°	90°
IP Rating	IP 23 open - IP 43 enclosed	IP 23 open - IP 43 enclosed
Power Factor	0.95	0.95
Starting /Running Amp	2.60 A - 1.35 A	4.20 A - 2.10 A
Suggested mounting height	4 - 5m Max	4 - 5m Max

## RL606 LOWBAY

### Specifications

Product Code	RL606250MH/HPS	RL606400MH/HPS	RL60685/105CFL
Approx System Wattage	250W MH/HPS	400W MH/HPS	85W - (E40) - 105W (E40)
Absolute Lumens	19000lm ( MH) - 27000lm ( HPS)	35000lm ( MH) - 48000lm ( HPS)	5100lm ( 85W) - 6000lm (105W)
Colour Temperature	4800K	4800K	6500K
CRI	≥80	≥80	≥80
Life Span	35000hrs	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°	min -20° max +35°
Housing Material	Powder coated mild steel body	Powder coated mild steel body	Powder coated mild steel body
Packaging Weights and dimensions	353mm x 178mm x 616mm @ 7.65Kg	353mm x 178mm x 616mm @ 9.55Kg	353mm x 178mm x 616mm @ 3.25Kg
Beam Angle	60°	60°	60°
IP Rating	IP 23 open - IP 43 enclosed	IP 23 open - IP 43 enclosed	IP 23 open - IP 43 enclosed
Power Factor	0.95	0.95	0.95
Starting /Running Amp	(2.80 A - 1.42 A) - (2.10 A - 1.42 A)	(3.80 A - 2.20 A) - (3.80 A - 2.20 A)	0.60 A - 038 A
Suggested mounting height	4 - 5m Max	4 - 5m Max	4 - 5m Max