




RL707 FLOODLIGHT

Product details



60°



90°

Features

- Corrosion resistant glass reinforced polyester housing.
- Heat tempered glass.
- Integral control gear.
- High purity aluminium reflector.

Benefits

- Universal electroplated mounting stirrup with pole clamp.
- Ingress protection rating - IP 65.

Applications

Security
Perimeters
Signage
Small holdings
Parks & Gardens

Warranty

Reeflite glass reinforced polyester (GRP) housings are guaranteed for 15 years against deterioration due to ultra-violet radiation, hail damage and corrosion at coastal areas.

RL707 FLOODLIGHT

Specifications

Product Code	RL70770(I)HPS - RL70770HPS	RL70780MV	RL707125MV
Approx System Wattage	70W HPS - Internal / External Ignitor	80W MV	125W MV
Absolute Lumens	5600lm	3800lm	6200lm
Colour Temperature	4000K	4000K	4000K
CRI	≥70	≥70	>70
Life Span	TBA	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°	min -20° max +35°
Housing Material	Fibreglass	Fibreglass	Fibreglass
Packaging Weights and dimensions	362mm x 330mm x 265mm @ 6.40Kg	362mm x 330mm x 265mm @ 6.40Kg	362mm x 330mm x 265mm @ 6.40Kg
Beam Angle	60° - 90°	60° - 90°	60° - 90°
IP Rating	IP 65	IP 65	IP 65
Power Factor	0.95	0.95	0.95
Starting /Running Amp	0.72 A - 0.45 A	0.90 A - 0.45 A	1.35 A - 0.68 A
Suggested mounting height	2 - 5m Max	2 - 5m Max	2 - 5m Max