





RL717 FLOODLIGHT

Product details



60°



90°

Features

- Corrosion resistant glass reinforced polyester housing.
- Heat tempered glass.
- Integral control gear.
- High purity aluminium reflector.

Benefits

- Universal electroplated mounting stirrup with pole clamp.
- Ingress protection rating - IP 65.

Applications

Security
Perimeters
Signage
Small holdings
Parks & Gardens

Warranty

Reeflite glass reinforced polyester (GRP) housings are guaranteed for 15 years against deterioration due to ultra-violet radiation, hail damage and corrosion at coastal areas.

RL717 FLOODLIGHT

Specifications

Product Code	RL717150HPS	RL717150MH
Approx System Wattage	150W HPS	150W MH
Absolute Lumens	14000lm	12500lm
Colour Temperature	4000K	4000K
CRI	≥70	≥70
Life Span	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°
Housing Material	Fibreglass	Fibreglass
Packaging Weights and dimensions	362mm x 330mm x 265mm @ 7.25Kg	362mm x 330mm x 265mm @ 7.20Kg
Beam Angle	60° - 90°	60° - 90°
IP Rating	IP 65	IP 65
Power Factor	0.95	0.95
Starting /Running Amp	1.30 A - 0.88 A	1.70 A - 0.82 A
Suggested mounting height	3 - 6m Max	3 - 6m Max