




## RL737 MINI ENERGY SAVING FLOOD

### Product details



### Features

- Corrosion resistant glass reinforced polyester housing.
- Heat tempered glass.
- Integral control gear.
- High purity aluminium reflector.

### Benefits

- Wall mount electroplated stirrup.
- Ingress protection rating - IP 65.
- Pole clamp available.
- Black or white color options.
- Compact.

### Applications

Security  
Perimeters  
Signage  
Gardens

### Warranty

Reeflite glass reinforced polyester (GRP) housings are guaranteed for 15 years against deterioration due to ultra-violet radiation, hail damage and corrosion at coastal areas.

## RL737 MINI ENERGY SAVING FLOOD

### Specifications

Product Code	RL737226	RL737226 ELECTRONIC
Approx System Wattage	2x26w - 2 Pin lamp	2x26w - 4 Pin lamp
Absolute Lumens	3600lm	3600lm
Colour Temperature	4000K	4000K
CRI	≥80	≥80
Life Span	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°
Housing Material	Fibreglass	Fibreglass
Packaging Weights and dimensions	268mm x 249mm x 210mm @ 2.70Kg	268mm x 249mm x 210mm @ 2.70Kg
Beam Angle	90°	90°
IP Rating	IP 65	IP 65
Power Factor	0.95	0.95
Starting /Running Amp	0.40 A - 0.30 A	0.40 A - 0.30 A
Suggested mounting height	2 - 5m Max	2 - 5m Max