


## SUPER HIGHBAY

### Product details



22" acrylic diffuser



### Features

- Powder coated mild steel gear housing.
- Removable gear tray.
- 520mm anodised aluminium reflector with optional glass cover.

### Benefits

- Also available with 22" acrylic diffuser with aluminium ring adapter.
- Acrylic drop lens optional.
- Ingress protection rating - IP 23 open.
- Ingress protection rating - IP 43 enclosed.

### Applications

Warehouses  
Foundries  
Workshops & other industrial Installations

### Warranty

3 year warranty

## SUPER HIGHBAY

### Specifications

Product Code	RL254S250MV / RL254SAC250MV	RL254S400MV / RL254SAC400MV
Approx System Wattage	250W MV - E40	400W MV - E40
Absolute Lumens	12700lm	22000lm
Colour Temperature	4800K	4800K
CRI	≥80	≥80
Life Span	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°
Housing Material	Powder coated mild steel gear housing	Powder coated mild steel gear housing
Packaging Weights and dimensions	545mm x 545mm x 633mm @ 7.30Kg	545mm x 545mm x 633mm @ 8.30Kg
Beam Angle	90°	90°
IP Rating	IP 23 open - IP 43 enclosed	IP 23 open - IP 43 enclosed
Power Factor	0.95	0.95
Starting /Running Amp	2.60 A - 1.35 A	4.20 A - 2.10 A
Suggested mounting height	5 - 8m Max	5 - 8m Max

## SUPER HIGHBAY

### Specifications

Product Code	RL254S250MH/HPS / RL254SAC250MH/HPS	RL254S400MH/HPS / RL254SAC400MH/HPS
Approx System Wattage	250W MH/HPS - E40	400W MH/HPS - E40
Absolute Lumens	19000lm ( MH) - 27000lm ( HPS)	35000lm ( MH) - 48000lm ( HPS)
Colour Temperature	4800K	4800K
CRI	≥80	≥80
Life Span	TBA	TBA
Average temp	min -20° max +35°	min -20° max +35°
Housing Material	Powder coated mild steel gear housing	Powder coated mild steel gear housing
Packaging Weights and dimensions	545mm x 545mm x 633mm @ 8.50Kg	545mm x 545mm x 633mm @ 9.85Kg
Beam Angle	90°	90°
IP Rating	IP 23 open - IP 43 enclosed	IP 23 open - IP 43 enclosed
Power Factor	0.95	0.95
Starting /Running Amp	(2.80 A - 1.42 A) - (2.10 A - 1.42 A)	(3.80 A - 2.20 A) - (3.80 A - 2.20 A)
Suggested mounting height	5 - 8m Max	5 - 8m Max