



FITTING	LAMP & WATTAGE	MOUNTING HEIGHT	SPREAD IN DEGREES	DISTANCE AT MOUNTING HEIGHT FOR 1 LUX	LUMEN OUTPUT OF LAMP(S)
<b>RL045</b>	45W	4M	90	9M	2 900
	23W	3M	90	7M	1 450
	18W	3M	90	6M	1 150
	14W	3M	90	5.5M	780
<b>RL737</b>	70(i) HPS	5M	90	14M	5 600 (E)
	80 MV	5M	90	12M	3 800 (E)
	125 MV	5M	90	16M	6 200 (E)
	2 X 26 W	4M	90	10M	3 600 (E)
<b>RL717</b>	150 HPS	6M	70	22M	14 000 (T)
	150 MH	6M	70	20M	12 500 (E)
	150 HPS (wide beam)	6M	90	20M	14 000 (T)
	150 MH (wide beam)	6M	90	18M	12 500 (E)
<b>RL303</b>	250 MV	7M	90	24M	12 700 (E)
	400 MV	8M	90	32M	22 000 (E)
	250 HPS	7M	90	32M	25 000 (E)
	400 HPS	7M	90	40M	47 000 (E)
	85 CFL	5M	90	14M	51 00 (4-U)
	105 CFL	5M	90	16M	6 000 (4-U)
<b>RL101</b>	250 MH	8M	65	50M	19 000 (T)
	400 MH	10M	65	75M	35 000 (T)
	250 HPS	8M	65	55M	27 000 (T)
	400 HPS	10M	65	90M	48 000 (T)
	250 MH (wide beam)	8M	90	40M	19 000 (T)
	400 MH (wide beam)	10M	90	60M	35 000 (T)
	250 HPS (wide beam)	8M	90	50M	27 000 (T)
	400 HPS (wide beam)	10M	90	68M	48 000 (T)
<b>RL1000</b>	1000 HPS	20M	75	130M	130 000 (T)
	1000 MH	20M	75	115M	80 000 (T)
	1000 HPS (wide beam)	20M	90	100M	130 000 (T)
	1000 MH (wide beam)	20M	90	90M	80 000 (T)
<b>CF</b>	150 MH	6M	90	18M	12 500 (E)
	250 MH	7M	90	25M	19 000 (T)
	400 MH	10M	90	40M	35 000 (T)
	150 HPS	6M	90	22M	14 000 (T)
	250 HPS	7M	90	30M	27 000 (T)
	400 HPS	10M	90	56M	48 000 (T)
	250 MV	7M	90	20M	12 700 (E)
	400 MV	8M	90	30M	22 000 (E)
<b>EF</b>	2 X 18 W	4M	90	4.5M	1 200