


# RFM FLUORESCENT MOISTURE PROOF

1 x 18 W ■ 2 x 18 W ■ 1 x 36 W ■ 2 x 36 W ■ 1 x 58 W ■ 2 x 58 W



5 ft - 1573mm  
4 ft - 1277mm  
2 ft - 660mm



## APPLICATIONS

CORRIDORS & PASSAGEWAYS  
MOISTURE/CORROSIVE  
ENVIRONMENT  
DUSTY ENVIRONMENT  
CANOPY  
COLD ROOMS

**MOUNTING HEIGHT:** 2 - 4 m

- GRP base ■ acrylic diffuser ■ robust polyamide or stainless steel clips ■ roto lock lampholders
- removable powder coated gear plate ■ electromagnetic or electronic control gear ■ IP66 ■ T8 or T5 lamps

## ORDERING DATA

CODE	CORRECTED LINE CURRENT		WEIGHT
	STARTING	RUNNING	
RFM <b>118</b> (1 X 18 W)	0.17 A	0.13 A	1.50 KG
RFM <b>218</b> (2 X 18 W)	0.29 A	0.22 A	2.00 KG
RFM <b>136</b> (1 X 36 W)	0.29 A	0.22 A	3.00 KG
RFM <b>236</b> (2 X 36 W)	0.58 A	0.44 A	4.00 KG
RFM <b>158</b> (1 X 58 W)	0.42 A	0.32 A	3.50 KG
RFM <b>258</b> (2 X 58 W)	0.84 A	0.64 A	5.00 KG