


RL254 S SUPERBAY

250 MV ■ 400 MV ■ 250 HPS ■ 400 HPS ■ 250 MH ■ 400 MH



APPLICATIONS

WAREHOUSES

FOUNDRIES

FACTORIES

WORKSHOPS & OTHER
INDUSTRIAL INSTALLATIONS

MOUNTING HEIGHT: 5 m +

- powder coated mild steel gear housing ■ removable gear tray
- 520mm anodised aluminium reflector with optional glass cover ■ IP23 open ■ IP43 enclosed
- **also available with:** 22" acrylic diffuser with optional acrylic drop lens with aluminium adapter

ORDERING DATA

| CODE | CORRECTED LINE CURRENT | | WEIGHT |
|------------------------|------------------------|---------|---------|
| | STARTING | RUNNING | |
| RL254 S 250 MV | 2.60 A | 1.35 A | 7.30 KG |
| RL254 S 400 MV | 4.20 A | 2.10 A | 8.30 KG |
| RL254 S 250 HPS | 2.10 A | 1.42 A | 8.50 KG |
| RL254 S 400 HPS | 3.80 A | 2.20 A | 9.85 KG |
| RL254 S 250 MH | 2.80 A | 1.42 A | 8.50 KG |
| RL254 S 400 MH | 3.80 A | 2.20 A | 9.85 KG |